

# 10 Adapter im Lieferumfang:

Nr.	Ausgangsspannung Volt	Max. Stromstärke	Konnektor Maße	Notebooks
N01	10 V	3A	4.8*1.7*10.7 mm	<b>Asus:</b> 9.5V/2.315A, 9.5V/3A; <b>Sony:</b> 10.5V/1.9A
N04	19 V	4.74A	4.8*1.7*10.7 mm	<b>HP/COMPAQ:</b> 18.5V/2.7A, 18.5V/3.5A, 18.5V/3.8A, 18.5V/4.9A; <b>DELTA:</b> 19V/2.64A; <b>ASUS:</b> 19V/2.64A; <b>NEC:</b> 19V/2.64A
N06	16 V	5A	6.0*4.4*10.7 mm	<b>Panasonic:</b> 16V/2.5A, 15.1V/2.6A, 15.1V/2.64A; <b>Fujitsu:</b> 16V/2.5A, 16V/2.8A, 16V/3.36A, 16V/3.75A; <b>Sony:</b> 16V/2.5A, 16V/2.1A, 16V/3.75A, 16V/4A
N07	19 V	4.74A	5.5*2.5*10.7 mm	<b>BenQ:</b> 19V/2.1A; <b>Dell:</b> 18V/1.9A, 19V/2.4A, 19V/1.58A, 19V/3.16A; <b>HP:</b> 18V/2.3A, 19V/2.4A, 19V/3.16A; <b>Compaq:</b> 18V/1.9A, 18.5V/1.1A, 18.5V/4.9A, 19V/4.9A; <b>IBM:</b> 19V/2.4A, 18V/1.9A, 19V/3.16A, 19V/4.2A; <b>Toshiba:</b> 18V/1.1A, 18V/1.7A, 19V/1.58A, 19V/3.42A, 19V/4.74A; <b>Gateway:</b> 19V/3.16A, 19V/3.68A, 19V/4.74A; <b>Acer:</b> 19V/3.42A; <b>NEC:</b> 19V/2.64A, 19V/3.16A; <b>DELTA:</b> 19V/2.64A, 19V/3.42A; <b>Liteon:</b> 19V/3.16A, 19V/3.42A, 19V/3.95A, 19V/4.74A; <b>Epson:</b> 19V/1.23A
N09	19.5 V	4.62A	6.0*4.4*10.7 mm	<b>Sony:</b> 19.5V/2.15A, 19.5V/2.3A, 19.5V/3A, 19.5V/4.1A, 19.5V/4.7A; <b>Fujitsu:</b> 19V/3.16A, 19V/3.69A, 19V/4.22A
N13	15 V	5A	6.3*3.0*10.7 mm	<b>TOSHIBA:</b> 15V/3A, 15V/4A, 15V/5A; <b>NEC:</b> 15V/4A
N14	16 V	5A	5.5*2.5*10.7 mm	<b>IBM:</b> 16V/2.2A, 16V/1.88A, 16V/3.36A, 16V/3.5A, 16V/4.5A; <b>DELTA:</b> 15V/1A, 16V/3.5A, 16V/4.5A; <b>ACER:</b> 16V/3.75A
N18	19 V	4.74A	5.5*2.1*10.7 mm	<b>ACER:</b> 19V/3.16A, 19V/3.42A, 19V/4.74A; <b>LITEON:</b> 19V/3.16A, 19V/3.42A; <b>NEC:</b> 19V/3.16A
N19	19 V	4.74A	5.5*3.0*10.7 mm	<b>SAMSUNG:</b> 19V/3.16A, 19V/3.75A, 19V/4.22A, 19V/4.74A
N24	20 V	4.5A	7.9*5.5*0.9 mm	<b>IBM/LENOVO:</b> 20V/4.5A, 20V/3.25A

# Optionale Adapter:

Nr.	Navilock Artikel Nummer	Volt	Leistungsbereich	Konnektor Maße	Notebooks
N02	65133	12 V	11.4-12.6V	4.8*1.7*10.7 mm	<b>HP:</b> 12V/2.5A, 12V/3.5A; <b>Asus:</b> 12V/3A
N03	65331	20 V	19.0-20.0V	5.5*2.5*10.7 mm	<b>Lenovo:</b> 20V/1.2A; <b>IBM:</b> 20V/2A; <b>LG:</b> 20V/2A; <b>MSI:</b> 20V/2A; <b>LS:</b> 20V/3.25A
N05	65332	19 V	18.1-19.9V	4.0*1.7*10.7 mm	<b>HP:</b> 19V/1.58A
N08	65126	12 V	11.4-12.6V	5.5*2.5*10.7 mm	<b>Für Monitore:</b> 12V/1A, 12V/2A, 12V/2.5A, 12V/3A, 12V/3.5A, 12V/4A, 12V/5A, 12V/6A, 12V/8A
N10	65333	14 V	13.3-14.7V	6.0*4.4*10.7 mm	<b>DELL:</b> 14V/3A; <b>Samsung:</b> 14V/3A, 14V/4A
N11	65120	19.5 V	18.1-19.9V	5.5*1.7*10.7 mm	<b>TOSHIBA:</b> 19V/3.95A; <b>ACER:</b> 19V/3.42A; <b>DELTA:</b> 20V/3.5A
N12	65334	12 V	11.4-12.6V	4.0*1.7*10.7 mm	<b>Samsung:</b> 12V/3.5A; <b>KODAK:</b> 12V/2A
N15	65222	16.5 V	15.7-17.3V	Magnetic 5P	<b>Apple:</b> Mac book 5P 16.5V/3.65A
N16	65123	22 V	20.9-23.1V	3.5*1.35*9.5 mm	<b>SHARP:</b> 22V/1.8A, 22V/2.04A
N17	65132	19 V	18.1-19.9V	4.8*1.7*10.7 mm	<b>HP:</b> 18.5V/3.5A, 19V/4.74A
N20	65335	19 V	18.1-19.9V	2.35*0.7*9.0 mm	<b>Asus:</b> 19V/2.1A
N21	65330	18.5 V	17.6-19.4V	Magnetic 5P	<b>Apple:</b> Mac book 5P 18.5V/3.65A
N22	65121	19.5 V	18.5-20.4V	7.4*5.0*12.5 mm	<b>DELL:</b> 19.5V/3.34A, 19.5V/4.62A
N23	65125	18.5V	17.6-19.4V	7.4*5.0*12.5 mm	<b>HP/COMPAQ:</b> 18.5V/3.5A, 18.5V/4.9A
N25	65157	24 V	22.8-25.2V	7.7*2.5*4.3 mm	<b>Apple:</b> 24V/1.875A, 24V/2A, 24V/2.65A
N26	65158	24 V	22.8-25.2V	9.5*3.5*4.0 mm	<b>Apple:</b> 24V/1.875A, 24V/2A, 24V/2.65A
N27	65122	20 V	19.0-20.0V	7.3*7.4 mm 3 pin	<b>DELL:</b> 20V/3.5A, 20V/4.5A
N28	65329	15 V	14.3-15.7V	9.2*6.4 mm 4 pin	<b>Toshiba:</b> 15V/8A
N30	65131	14 V	13.3-14.7V	5.5*2.5*10.7 mm	<b>Samsung:</b> 14V/3A, 14V/3.5A