

SPECIFICATIONS
1.ELECTRICAL:
UL APPLICATIONS: 250 VOLTS AC MAX., AT 2 AMPS.
DIELECTRIC WITHSTANDING VOLTAGE : 1000 VOLTS AC.
WITHSTAND VOLTAGE TIME: 60S.
INSULATION RESISTANCE: 100 MΩ.
TERMINATION: RESISTANCE 20mΩ MAX AFTER ENVIRONMENTAL TESTING.
2.MECHANICAL:
CABLE-TO-PLUG TENSILE STRENGTH : 20POUND MIN.
DURABILITY : 200 MATING CYCLES.
3.MATERIAL & FINISH:
HOUSING: POLYCARBONATE, UL94V-0 OR UL94V-2.
COLOR : TRANSPARENT OR OTHER COLOR ARE AVAILABLE.
CONTACT BLADE: COPPER ALLOY.
CONDUCTOR : STRANDED & SOLID WIRE , 24AWG, 26 AWG.
(It can be used for the wire OD fromØ 0.96~Ø1.02)
GOLD PLATING: 3u"~50u",ARE AVAILABLE.
SHIELDED SHELL: COPPER ALLOY.

BLADE:	E	EB	Y	YB	Z	A	AE	AB	EC	AL	ZL	YBL
Drawing												
Mark					✓							

GOLD PLATING	3Mu"	3u"	6u"	15u"	30u"	50u"	CABLE TYPE	ROUND	FLAT
Mark						✓	Mark		✓

Date	2018 / 02 / 22
Unit	mm
Projection	
Rev	A

DELOCK® we move the world

Title:	RJ45 Crimp+Cut Plug Cat.6 STP
Item no.	86454
Barcode	4043619864546