

This crimping profile insert is an accessory for the Delock crimping pliers 90528, 90527, 90295 and 90296. The rubberised handles provide a firm grip during the crimping process. The crimping profile insert, the so-called jaws, are interchangeable so that the right pair can be fitted for each application.

90529
Hex crimp size: 9.14 mm (.360"), 8.23 mm (.324"), 6.65 mm (.262"), 1.73 mm (.068")
Coaxial cable suitable for crimping RG-59, RG-6
Material: 40Cr
Connectors suitable for crimping: e.g. F connectors



90530
Oval crimp size: 4.95 mm (.195"), 4.11 mm (.162"), 3.38 mm (.133"), 1.73 mm (.068"), 1.07 mm (.042")
Coaxial cable suitable for crimping RG-58, RG-59, RG-62, RG-6
Material: 40Cr
Connectors suitable for crimping: Fiber optic SMA (oval)



90531
Hex crimp size: 8.23 mm (.324"), 4.52 mm (.178"), 1.73 mm (.068")
Coaxial cable suitable for crimping RG-58, RG-6, RG-174
Material: 40Cr
Connectors suitable for crimping: e.g. SMA, SMB




90532
Hex crimp size: 5.41 mm (.213"), 4.52 mm (.178"), 3.84 mm (.151"), 1.73 mm (.068"), 1.07 mm (.042")
Coaxial cable suitable for crimping RG-58, RG-174, Belden 8281
Material: 40Cr
Connectors suitable for crimping: e.g. Fiber optic SMA, SMB




90533
Hex crimp size: 6.48 mm (.255"), 5.41 mm (.213"), 3.48 mm (.137"), 2.54 mm (.100"), 1.73 mm (.068"), 1.07 mm (.042")
Coaxial cable suitable for crimping RG-58, RG-59, RG-62, RG-174
Material: 40Cr
Connectors suitable for crimping: Fiber optic e.g. LC, SC



90535
Hex crimp size: 5.41 mm (.213"), 3.84 mm (.151"), 3.25 mm (.128"), 2.54 mm (.100"), 1.75 mm (.069"), 1.09 mm (.043")
Coaxial cable suitable for crimping RG-58, RG-59, RG-174
Material: 40Cr
Connectors suitable for crimping: e.g. SMB, SMA, SMC, MCX



90536
Cable suitable for crimping: AWG 22 - 18, 16 - 14, 12 - 10
Material: 40Cr
Connectors suitable for crimping: e.g. Cable lugs, connection terminal, wire clamps, crimp connectors



90537
Cable suitable for crimping: AWG 22 - 18, 16 - 14, 12 - 10
Diameter: 1.25 - 5.5 mm ²
Material: 40Cr
Connectors suitable for crimping: e.g. flat receptacles, copper sleeve



90538
Cable suitable for crimping: AWG 14 - 22
Diameter: 0.5 - 2.5 mm ²
Material: 40Cr
Connectors suitable for crimping: e.g. Terminal crimp contacts for D-Sub



90539
Cable suitable for crimping: AWG 22 - 18, 16 - 14, 12 - 10
Diameter: 0.5 - 1.0 / 1.5 - 2.5 / 4.0 - 6.0 mm ²
Material: 40Cr
Connectors suitable for crimping: e.g. Cable lugs, connection terminal, wire clamps, crimp connectors



90528
Universal Coax Crimping Tool for 4 different diameters angled
Coaxial cable suitable for crimping RG-58, RG-59, RG-62, RG-6
Connectors suitable for crimping: e.g. SMA, SMB
Hex crimp size: 8.23 mm (.324"), 6.50 mm (.256"), 5.41 mm (.213"), 1.73 mm (.068")



90295
Universal Coax Crimping Tool for 6 different diameters
Coaxial cable suitable for crimping RG-58, RG-59, RG-62, RG-174, RG-140, RG-400
Connectors suitable for crimping: e.g. SMA, SMB
Hex crimp size: 6.48 mm (.255"), 5.41 mm (.213"), 3.50 mm (.137"), 2.54 mm (.100"), 1.73 mm (.068")

