

Delock WLAN 802.11 a/ax/a/b/g/n Antenna RP-SMA plug 5 dBi 20 cm omnidirectional with tilt joint flexible and rubber surface black

Description

This Wireless LAN antenna by Delock can be connected to a WLAN device with RP-SMA interface, in order to send and receive signals.

Bluetooth



Item no. 12636

EAN: 4043619126361

Country of origin: China

Package: Retail Box

Technical details

- Connector: 1 x RP-SMA plug
- Frequency range:
 - 2.400 - 2.500 GHz
 - 5.150 - 5.850 GHz
- Antenna gain: 5 dBi
- Impedance: 50 Ohm
- Polarisation: linear, vertical
- VSWR: 2.5
- Operating temperature: -10 °C ~ 70 °C
- Colour: black
- Length:
 - ca. 200 mm (with tilt joint)
 - ca. 177 mm (without tilt joint)
- Diameter:
 - ca. 12.70 mm (RP-SMA)

















System requirements

- Device with a free RP-SMA jack

Package content

- WLAN antenna

Images



General

Mounting type:	Screw mounting
Suitable for indoor:	yes

Interface

connector:	1 x RP-SMA plug
------------	-----------------

Technical characteristics

Frequency range:	5150 MHz - 5850 MHz 2400 MHz - 2500 MHz
Antenna gain:	5 dBi
Impedance:	50 Ω
Operating temperature:	-10 °C ~ 70 °C
Polarisation:	linear vertical
VSWR:	2.5

Physical characteristics

Antenna type:	omnidirectional
Housing material:	ABS
Length:	20 cm
Diameter connector:	12.7 mm
Colour:	black