


Delock Adapter M.2 Key B+M male to CFexpress Slot

Description

This adapter by Delock can be used to connect a **CFexpress memory card** to the **M.2 interface**. Through the predetermined breaking point, the length can be shortened from 80 mm to 60 mm.



Item no. 21360

EAN: 4043619213603 Country of origin: Taiwan,

Republic of China Package: Retail Box

Technical details

- Connectors:
 - 1 x M.2 key B+M male
 - 1 x CFexpress 2.0 slot type B
- Interface: PCIe Rev. 3.0
- Form factor: 2280 or 2260
- Suitable for M.2 slot with key M or B based on PCIe
- Push to push CFexpress socket
- Supports NVM Express (NVMe)
- LED indicator for power
- Bootable, ex UEFI version 2.3.1
- Dimensions (LxWxH): ca. 80 x 37 x 5 mm

System requirements

- Linux Kernel 3.17 or above
- Windows 8.1/8.1-64/10/10-64/11
- A free M.2 key M or key B slot





Package content

- Adapter
- User manual

Images











General

| Form factor: | M.2 2280 |
|-----------------------------|---|
| Function: | Bootable, ex UEFI 2.3.1 |
| Supported operating system: | Linux Kernel 3.17 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11 |
| LED indicator: | power and activity |
| Supported memory card: | CFexpress |

Interface

| Connector 1: | 1 x M.2 key B+M male |
|--------------|----------------------|
| Connector 2: | 1 x CFexpress slot |