

Delock USB Charger 1 x USB Type-C™ PD 85 W + 3 x USB Type-A Qualcomm Quick Charge 3.0

Description

This USB Power Delivery (PD) charger by Delock can be used to charge laptops with USB Type-C™ connector. It provides various voltages from 5 V to 20 V and power up to 85 Watt. In addition, 3 USB Type-A 5 V connectors with Qualcomm Quick Charge 3.0 charging technology are available for smartphones.

With special charging technology, the power supply can also be used to power conventional laptops. Included are 11 different DC adapters, which are suitable for different laptops. With this versatile power supply, all mobile devices can be charged from a single socket.

Note

Compatible with:

N04 19 V 4.8 x 1.7 x 10.7 mm

HP/Compaq: 18.5 V / 2.7 A, 18.5 V / 3.5 A

Delta: 19 V / 2.64 A

ASUS: 19 V / 2.64 A

NEC: 19 V / 2.64 A

N07 19 V 5.5 x 2.5 x 10.7 mm

Dell: 19 V / 3.16 A, 19 V / 3.42 A

Delta: 19 V / 2.64 A

Toshiba: 19 V / 3.16 A, 19 V / 3.42 A

LiteOn: 19 V / 3.16 A, 19 V / 3.42 A

NEC: 19 V / 2.64 A, 19 V / 3.16 A

Gateway: 19 V / 3.16 A, 19 V / 3.42 A

N09 19.5 V 6.0 x 4.3 x 10.7 mm

Sony: 19.5 V / 2.7 A, 19.5 V / 3 A

Fujitsu: 19 V / 3.16 A

N11 19 V 5.5 x 1.7 x 10.7 mm

Acer: 19 V / 3.42 A

Delta: 20 V / 3.5 A

N18 19 V 5.5 x 2.1 x 10.7 mm

Acer: 19 V / 3.16 A, 19 V / 3.42 A

LiteOn: 19 V / 3.16 A, 19 V / 3.42 A

NEC: 19 V / 3.16 A



Item no. 41431

EAN: 4043619414314

Country of origin: China

Package: Retail Box

N19 19 V 5.5 x 3.0 x 10.7 mm

Samsung: 19 V / 3.16 A

N22 19.5 V 7.4 x 5.0 x 12.5 mm

Dell: 19.5 V / 3.34 A, 19.5 V / 4.62 A

N23 18.5 V 7.4 x 5.0 x 12.5 mm

HP/Compaq: 18.5 V / 3.5 A

N24 20 V 7.9 x 5.5 x 0.9 mm

IBM/Lenovo: 20 V / 3.25 A

N35 20 V 11 x 5.6 x 11 mm

Lenovo: 20 V / 2.25 A, 20 V / 3.25 A

N36 19.5 V 4.5 x 3.0 mm

HP: 19.5 V / 2.31 A, 19.5V / 3.33 A

Technical details

- Connectors:
 - 1 x USB Type-C™ female
 - 3 x USB Type-A female
 - 1 x IEC-60320-C8 connector
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 2.0 A
- Output:
 - USB Type-C™ Power Delivery (PD): 5 V
 - 5.0 V / 4.0 A, 9.0 V / 12.0 V / 15.0 V / 20.0 V 4.3 A
 - USB Type-A Qualcomm Quick Charge 3.0 Class A:
 - 3.6 ~ 6.5 V / 3.0 A, 9.0 V / 2.0 A, 12.0 V / 1.5 A
- Output power: max. 87.0 W total
- Average active efficiency 80.46 %
- Efficiency at low load (10 %) 65.97 %
- No-load power consumption 0.16 W
- Over load protection
- Over current protection
- Overheating protection
- Short circuit protection
- Colour: black
- Dimensions (LxWxH): ca. 110 x 98 x 20 mm

Package content

- USB charging station
- Power cord

- Bag
- Stand
- USB Type-C™ PD cable, length ca. 1 m
- USB Type-C™ DC cable, length ca. 1 m
- 11 x DC adapter
- User manual

Images



Physical characteristics

Housing colour:	black
-----------------	-------

Power supply

Type:	Power supply with IEC connector
Input:	AC 100 - 240 V / 50 - 60 Hz / 1,5 A
Output:	5 V / 4 A 12 V / 1.5 A 3.6 ~ 6 V / 3 A 9 V / 2 A 9 ~ 20 V / 4.3 A
Connector:	1 x USB Type-C™ female 3 x USB type-A female