

Navilock GNS602 MT3339 TTL GPS Engine Module PPS

Description

This engine module concerns a complete GNSS receiver and including a patch.....



Item no. 60546

EAN: 4037735104662

Country of origin:
GERMANY

Package: Retail Box

Special features

- Logger Function
- PPS (Puls per Second)
- Up to 10Hz

Technical details

- Chipset: MT3339
- N_{avg} -165 dB
- TTL 3,3V
- Concurrent receipt 22/Tracking, 66/Acquisition Satellites
- Active interference cancellation (MTAIC)
- NMEA: GPRMC, GPGSA, GPGSV, GPGGA, GPVTG
- SBAS (SBAS: WAAS, GAGAN, MSAS, QZSS)

* Logger Function 128KB/line (10s)

- Position accuracy 2,50 m
- PPS (Puls per Second)
- Update Rate 1/s , 9600 bps (default)
- Real time clock intern (RTC)
- A-GPS (Internet required)
- TTFF (Time to first FIX)
Cold 35s

- Warm 34s
 - Hot 1s
 - Current tracking: 20 mA @ 3,30 V
 - Footprint: 16,00 x 16,00 x 5,20 mm
 - Height: 5,20 x 3,70 x 0,70 mm
 - Operating temperature: -40 °C ~ 85 °C
-

System requirements

- No system required
-

Package content

- CD
 - GNSS module
-

Images

