

# Delock USB to SATA 6 Gb/s Converter with USB Type-C™ or USB Type-A connector

## Description

This Delock converter can be connected via **USB-C™** or **USB Type-A** interface to a PC or laptop. Thus a **2.5" SATA HDD or SSD** with a 22 pin SATA interface can be used.

## Extensive connectivity

Due to the specially designed adapter, the Delock converter can be quickly and easily connected to the USB Type-A socket. Thus, it can be easily connected to new devices with USB Type-C™ female and older devices that only have a USB Type-A connector. The adapter is located directly on the cable and therefore it cannot be lost.



**Item no. 61042**

EAN: 4043619610426

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - 1 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) USB Type-C™ male
  - 1 x SATA 6 Gb/s 22 pin receptacle
- Adapter:
  - 1 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) USB Type-C™ female
  - 1 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) Type-A male
- Chipset: Asmedia ASM1153e
- Suitable for 2.5" SATA HDD / SSD
- Supports SATA 1.5 Gb/s, SATA 3 Gb/s and SATA 6 Gb/s
- Data transfer rate up to 5 Gb/s
- Plug & Play
- Length incl. connectors: ca. 30 cm

## System requirements

- Android 11.0 or above
- Chrome OS

- Linux Kernel 5.13 or above
- Mac OS 12.2.1 or above
- Windows 8.1/8.1-64/10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 port or
- A free USB Type-A port

---

## Package content

- Converter
- Cover cap
- User manual

---

## Images



## General

|                             |   |
|-----------------------------|---|
| Suitable for data medium:   | 2.5"  |
| Supported operating system: | Chrome OS<br>Surface Pro 7<br>Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit<br>iPad Pro (3rd Generation) or above<br>iPad Air (4th Generation) or above<br>Windows 11<br>Linux Kernel 5.13 or above<br>Mac OS 12.2.1 or above<br>Android 11.0 or above |

## Interface

|              |                                   |
|--------------|-----------------------------------|
| Connector 1: | 1 x USB 5 Gbps USB Type-C™ male   |
| Connector 2: | 1 x SATA 6 Gb/s 22 pin receptacle |

## Technical characteristics

|                     |                  |
|---------------------|------------------|
| Chipset:            | Asmedia ASM1153E |
| Data transfer rate: | 5 Gbps           |

## Physical characteristics

|                               |       |
|-------------------------------|-------|
| Cable length incl. connector: | 30 cm |
|-------------------------------|-------|