

Navilock NL-302U USB GPS Receiver

Description

The USB GPS receiver based on SiRFstarIII™ chipset has a built-in antenna for high sensitivity.

You can use this GPS Receiver with a Notebook and a suitable routing software for navigation.



Item no. 61422

EAN: 4043619614226

Country of origin: Taiwan,
Republic of China

Package: Retail Box

Special features

Please note that the SiRFstarIII chipset used here has reached the end of its production cycle. This receiver is delisted in the next few weeks.

Technical details

- SiRFstarIII™ high performance and low power chipset
- Accepts the signals of up to 20 satellites at the same time
- Supports NMEA 0183 protocols: GGA, GSA, GSV, RMC, GLL, VTG
- USB specification 1.1
- 4800 Baud
- IPX6 protection class
- Magnetic, non-slip on the bottom
- LED-indicator for GPS-status
- Cold start in about 42 sec.
- Warm start in about 38 sec.
- Hot start in about 1 sec.
- Dimension (LxWxH): 65 mm x 45 mm x 22 mm
- Cable length: 1.50 m

System requirements

- Windows 98/ME/2000/XP/Vista/7/8, Linux ex Kernel 2.6, Mac OS 8, 9, 10x
- PC or Notebook with a free USB Port

Package content

- USB GPS Receiver
- Driver CD
- User manual

Images

