

# Delock Adapter USB 2.0 Type-A > 2 x Serial DB9 RS-232

## Description

This USB Type-A to serial adapter by Delock provides two RS-232 DB9 interfaces for printers, measuring instruments, controllers, IoT devices etc.



1,5 m

**Item no. 63466**

EAN: 4043619634668

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - 1 x USB 2.0 Type-A male >
  - 2 x serial RS-232 DB9 male
- Chipset: FTDI FT232
- Data transfer rate up to 921.6 Kbps
- Supports: UHCI / OHCI / EHCI
- Serial connector with screw
- Supports remote wake-up and power management
- Cable length incl. connectors: ca. 1.5 m


## System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64/11, Linux ex Kernel 2.6.x, Mac ex OS 10.9
- PC or laptop with a free USB Type-A port

## Package content

- USB 2.0 to 2 x serial adapter
- Driver CD
- User manual

## Images



## General

Function:	Plug & Play Remote Wake-Up
Specification:	RS-232 (EIA / TIA) USB 2.0
Supported operating system:	Linux Kernel 2.6 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit
LED indicator:	power and activity

## Interface

Connector 1:	1 x USB 2.0 Type-A male
Connector 2:	2 x serial RS-232 DB9 plug

## Technical characteristics

Chipset:	FTDI FT232RL
Data transfer rate:	1 Mbps
FIFO:	2 x 256 Byte receive 2 x 128 byte transmit
Data transmission:	asynchronous full duplex

## Physical characteristics

Connector color:	yellow green
Housing material:	Plastic

Cable type:	USB AWM Style 2725
Cable colour:	black
Cable length incl. connector:	1.5 m
Conductor gauge:	26 AWG data line 24 AWG power line
Screw type:	#4-40 UNC