

Delock USB Type-C™ Adapter to HDMI (DP Alt Mode) 8K with HDR and Power Delivery 100 W

Description

This adapter by Delock is suitable for the connection of a HDMI monitor in **8K Ultra HD** (7680 x 4320 @ 60 Hz) resolution to a computer with USB-C™ interface and **DisplayPort alternate mode** support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt™ 3 interface.



USB Power Delivery (USB PD 3.0) support up to 100 watt

The adapter has a USB Type-C™ Power Delivery port to connect the power supply of the laptop or tablet to charge it. The adapter can also be used without a power supply.

Item no. 64199

EAN: 4043619641994

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - 1 x USB Type-C™ male
 - 1 x HDMI-A female
 - 1 x USB Type-C™ PD female (power supply)
- Chipset: Synaptics VMM7100
- DisplayPort 1.4 specification
- Resolution:
 - with DSC:
 - 7680 x 4320 @ 60 Hz
 - 3840 x 2160 @ 144 Hz
 - without DSC:
 - 7680 x 4320 @ 30 Hz
 - 3840 x 2160 @ 120 Hz
- (depending on the system and the connected hardware)
- Transmission of audio and video signals
- Supports 3D displays
- Supports HDR10
- Supports HDCP 1.4 and 2.2
- Output power for host: max. 100 W

- Plug & Play
- Housing material: aluminium
- Cable length without connectors: ca. 15 cm
- Colour: black

System requirements

- Android 11.0 or above
- Chrome OS
- Linux Kernel 5.11 or above
- Mac OS 12.2.1 or above
- Windows 8.1/8.1-64/10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- USB-C™ to HDMI adapter
- User manual

Images



General

| | |
|-----------------------------|---|
| Function: | Plug & Play HDR / HDR10 |
| Supported operating system: | Chrome OS Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 Linux Kernel 5.11 or above Mac OS 12.2.1 or above Android 11.0 or above |

Interface

| | |
|--------------|---------------------------------------|
| Connector 1: | 1 x USB Type-C™ male |
| Connector 2: | 1 x HDMI female |
| connector 3: | 1 x USB Type-C™ Power Delivery female |

Technical characteristics

| | |
|----------------------------|---------------------|
| Chipset: | Synaptics VMM7100 |
| Maximum screen resolution: | 7680 x 4320 @ 60 Hz |