

# Delock USB 10 Gbps Docking Station for 2.5" / 3.5" SATA HDD / SSD or M.2 NVMe PCIe or SATA SSD with fan

## Description

This docking station by Delock enables an external connection of one **2.5" or 3.5" SATA HDD or SSD** or one **M.2 NVMe or SATA SSD** through the **USB interface**. This solution does not require an external enclosure since the drive can be plugged into the docking station directly.

## Good cooling

A **large fan**, which is located directly behind the inserted memory, ensures sufficient cooling of the SSD or HDD. The fan can be switched on or off separately.

## Extensive connectivity

Due to the specially designed adapter, the Delock docking station can be quickly and easily connected to the USB Type-A socket. Thus, it can be easily connected to new devices with USB Type-C™ female and older devices that only have a USB Type-A connector. **The adapter is located directly on the cable** and therefore it cannot be lost.



**Item no. 64280**

EAN: 4043619642809

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - 1 x USB 10 Gbps USB Type-C™ female
  - 1 x SATA 6 Gb/s 22 pin receptacle
  - 1 x M.2 key M slot
  - 1 x DC jack
- Adapter:
  - 1 x USB 10 Gbps USB Type-C™ female
  - 1 x USB 10 Gbps Type-A male
- Chipset: Realtek RTL9210B
- Function key:
  - 1 x On / Off switch

- 1 x on / off switch for the fan
  - For 2.5" and 3.5" SATA HDD / SSD
  - Suitable for all SATA HDDs up to SATA 6 Gb/s
  - Supports M.2 modules with key M or key B+M based on SATA or PCIe (NVMe)
  - It can only be used one memory, not both at the same time
  - Bootable
  - Data transfer rate up to 10 Gbps
  - LED indicator for power and access
  - 1 x 80 x 80 mm fan
  - Dimensions (LxWxH): ca. 166 x 110 x 108 mm
  - Plug & Play
- 

## Power supply specification

- Wall power supply
  - Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.6 A
  - Output: 12.0 V / 2.0 A / 24.0 W
  - Ground outside, plus inside
  - Dimensions:
    - inside:  $\varnothing$  ca. 2.1 mm
    - outside:  $\varnothing$  ca. 5.5 mm
    - length: ca. 10 mm
- 

## System requirements


- Android 13.0 or above
  - Chrome OS
  - Linux Kernel 6.2 or above
  - Mac OS 12.4 or above
  - Windows 10/10-64/11
  - iPad Air (4th Generation) or above
  - iPad Pro (3rd Generation) or above
  - Surface Pro 7
  - Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 or Thunderbolt™ 4 port or
  - A free USB Type-A port
- 

## Package content

- Docking station

- Cable USB-C™ male to USB-C™ male (with adapter to USB Type-A male), length ca. 80 cm
- External power supply 12.0 V / 2.0 A
- User manual

## Images



## General

Function:	Plug & Play bootable
Suitable for data medium:	2.5" 3.5" SSD or HDD
Supported operating system:	Chrome OS Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 Mac OS 12.4 oder höher Linux Kernel 6.2 or above Android 13.0 or above

## Interface

External:	1 x DC jack 1 x USB 10 Gbps USB Type-C™ female
Internal:	1 x SATA 6 Gb/s 22 pin receptacle 1 x M.2 key M slot

## Technical characteristics

Chipset:	Realtek RTL9210B
Data transfer rate:	10 Gbps

## Physical characteristics

Housing material:	Plastic
Length:	166 mm
Width:	110 mm
Height:	108 mm
Colour:	black / grey