

# Delock Vlog Shotgun Microphone Set for Smartphones and DSLR Cameras

### Description

This professional condenser directional microphone by Delock can be used for high-quality voice and vocal recordings.

#### **Optimal recordings**

The microphone has a supercardioid polar pattern and therefore captures the sound ideally. Due to its high power, low self-noise and precise performance, even the finest sounds are recorded crystal clear. Annoying background noises are minimized.

#### Good windscreen

Due to the included windscreen, the recording quality is further optimized. Disturbing wind noises are optimally filtered.

#### **High compatibility**

With its 3.5 mm 4 pin stereo jack male, the microphone is compatible with various smartphones. Due to the included 3.5 mm TRS female adapter, the microphone can also be connected to various DSLR cameras and computers. With the hot shoe adapter, the microphone can be mounted on an accessory shoe of cameras.

#### No batteries required

The microphone is passive and therefore does not need batteries. This eliminates the need to change batteries.

#### Stable & non-slip stand

The metal stand with rubber feet ensures that the microphone stands firmly on the table. The adjustable smartphone clamp ensures a smooth recording. The rubberized clamps prevent smartphones from being scratched. The flexible smartphone clamp holds devices with a width of up to 8.5 cm. The ball joint can be rotated by 360° and locked in place. The table stand can be easily unscrewed and folded up when needed.



#### Item no. 66582

EAN: 4043619665822 Country of origin: China Package: Retail Box

### **Technical details**

© 2024 by Navilock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.



- Connector: 1 x 3.5 mm 4 pin stereo jack female
- Coiled Cable:
  - 1 x 3.5 mm 4 pin audio stereo jack male >
  - 1 x 3.5 mm 4 pin audio stereo jack male
- Adapter:
  - 1 x 3.5 mm 4 pin stereo jack female >
  - 1 x 3.5 mm 3 pin stereo jack male (TRRS to TRS)
- Directivity: supercardioid
- Sensitivity: -23 dB +/- 3 dB
- Frequency range: 20 Hz 12 kHz
- Signal-to-noise ratio (SNR): ca. 70 dB
- Sound pressure level (SPL): max. 110 dB
- Metal stand: Ø ca. 180 mm
- Microphone length: ca. 150 mm
- Smartphone clamp: width up to 8.5 cm
- · Hot shoe adapter for mounting on cameras with accessory shoe

### System requirements

• A free stereo port 3.5 mm

### Package content

- Microphone
- Stereo jack adapter
- Coiled cable, length ca. 10 cm 60 cm
- Table stand
- Flexible smartphone clamp
- Windscreen
- User manual

#### Images



© 2024 by Navilock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.



### Interface

connector:	1 x 3.5 mm 4 pin stereo jack female
Connector 2:	1 x 3.5 mm 4 pin audio stereo jack male

### **Technical characteristics**

Frequency range:	20 Hz - 12 kHz
Sensibility:	-23 dB +/- 3 dB
Signal noise ratio (SNR):	ca. 70 dB
Directivity:	Supercardioid

## **Physical characteristics**

Housing material:	metal
Cable colour:	black
Cable length:	ca. 10 cm - 60 cm
Length:	150 mm
Colour:	black