

# Delock Media Converter 10/100/1000Base-T to 100/1000Base-X SFP

## Description

This Gigabit Ethernet Media Converter by Delock can be used to expand a network with an optical fiber interface. In the SFP slot, an optional 100 Mb/s or 1 Gb/s SFP module can be used.



**Item no. 86110**

EAN: 4043619861101

Country of origin: China

Package: White Box

## Technical details

- Connectors:
  - 1 x SFP slot for 100/1000Base-X SFP module (SFP module not included)
  - 1 x RJ45 jack for 10/100/1000 Mb/s Base-T
  - 1 x DC jack 5.5 x 2.1 mm (power)
- Data transfer rate up to 1 Gb/s
- 6 LEDs for status monitoring
- DIP-switch for configuration of LFP (Link Fault Pass Through)
- Supports IEEE 802.3 / 802.3u / 802.3ab / 802.3z
- Power consumption: 2.5 W
- Metal housing
- Fanless
- Operating temperature: 0 °C ~ 55 °C
- Dimensions (LxWxH): ca. 94 x 70 x 26 mm

## Power supply specification

- Wall power supply

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.2 A
  - Output: 5 V / 1 A
  - Ground outside, plus inside
  - Dimensions:
    - inside:  $\varnothing$  ca. 2.1 mm
    - outside:  $\varnothing$  ca. 5.5 mm
    - length: ca. 9.5 mm
- 

## System requirements

- 100/1000Base-X SFP module
  - Device with one free RJ45 port
- 

## Package content

- Media Converter
  - Power supply
  - User manual
- 

## Images



## Interface

Output:	1 x SFP jack
Input:	1 x 5 V DC female 5,5 mm x 2,1 mm 1 x RJ45 jack

## Technical characteristics

Data transfer rate:	Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1 Gbps
---------------------	---

## Physical characteristics

Housing colour:	black
Housing material:	metal
Length:	94 mm
Width:	70 mm
Height:	26 mm

## Power supply

Type:	Euro wall power supply
Input:	AC 100 - 240 V / 50 - 60 Hz / 0.25 A
Output:	5 V / 1.25 A
Connector:	DC male 5.5 mm x 2.1 mm