

# Delock Serial Cable RS-232 D-Sub9 male to female with narrow plug housing 0.5 m

## Description

This serial cable by Delock is suitable as a **connection cable** for modem, printer, measuring instruments, converters, RS-232 hubs, patch panels etc.

### Mini D-Sub9 connector

These cables fit any RS-232 port, as the **mini D-Sub9 connectors** (44 x 33.3 x 15 mm) are small and compact. In this way, RS-232 connections can be used directly adjacent to each other.



0,5 m

**Item no. 87819**

EAN: 4043619878192

Country of origin: China

Package: Zip poly bag

## Technical details

- Connectors:
  - 1 x serial D-Sub9 male with nuts >
  - 1 x serial D-Sub9 female with screws
- Cable gauge: 28 AWG
- Pin assignment: 1:1
- Colour: black
- Insulator: PVC
- Screw type: #4-40 UNC
- Cable diameter: ca. 5 mm
- Cable length incl. connectors: ca. 0.5 m

## System requirements

- A free D-Sub9 port

## Package content

- Cable

---

## Images



## General

Specification:	RS-232 (EIA / TIA)
Style:	Connection cable Mini Sub-D9

## Interface

Connector 1:	1 x serial Sub-D 9 male with nuts
Connector 2:	1 x serial Sub-D 9 female with screws

## Physical characteristics

Cable type:	AWM Style 2464 28 AWG 80 °C 300 V VW-1
Cable length incl. connector:	0.5 m
Pin finishing:	gold-plated
Conductor material:	Copper tinned
Conductor gauge:	28 AWG
Screw type:	#4-40 UNC
Shielding:	Aluminum foil
Colour:	black
Cable jacket material:	PVC
Safety of Flammability:	VW-1