

# Delock USB 2.0 Data and Fast Charging Cable USB Type-C™ male to male PD 3.1 140 W with power indication 1.20 m

## Description

This USB cable by Delock enables the connection between a device with a USB Type-C™ connector and a PC or a laptop equipped with a free USB Type-C™ port. The integrated chipset supports the **PD 3.1** function for **fast charging** with a charging power of up to **140 W**. The cable supports the transfer of USB as well as DisplayPort and PCI Express data.



## Display

A special feature of this cable is the **power indication**, which shows the current charging power in watts as well as the current in amperes and voltage in volts. The power will be displayed with **three digits**.

**Item no. 88136**

EAN: 4043619881369

Country of origin: China

Package: Retail Box

## Quality and performance

The cable is very sturdy and durable due to its robust textile shielding and strong strain relief. The high cable gauge of the power line with 20 AWG also supports a stable power supply of up to 5 A.

## Technical details

- Connectors:
  - 1 x USB Type-C™ male
  - 1 x USB Type-C™ male
- Chipset: E-Marker BJ8M601AFE-BK1
- Cable gauge:
  - 28 AWG data line
  - 20 AWG power line
- USB Power Delivery (USB PD 3.1) support up to 140.0 watt (28.0 V / 5.0 A)
- Cable diameter: ca. 3.8 mm
- Data transfer rate up to 480 Mbps
- Cable with textile shielding
- Colour: black
- Length incl. connectors: ca. 1.20 m

---

## System requirements

- PC or laptop with a free USB Type-C™ port
- Power supply with a free USB Type-C™ port
- Device with USB Type-C™ port

---

## Package content

- Cable

---

## Images



## General

Cable finishing:	textile coating
Specification:	USB 2.0

## Interface

connector:	1 x USB 2.0 Type-C™ male
Connector 1:	1 x USB 2.0 Type-C male

## Technical characteristics

Data transfer rate:	480 Mbps
Maximum load:	140 W
Maximum current:	5 A
Voltage:	28 V

## Physical characteristics

Cable length incl. connector:	1.20 m
Conductor gauge:	28 AWG data line 20 AWG power line
Colour:	black