


# Delock PCI Express x4 Card > 1 x internal NVMe M.2 Key M 110 mm - Low Profile Form Factor

## Description

The Delock PCI Express card expands a PC by one M.2 slot. A M.2 SSD in format 22110, 2280, 2260, 2242 and 2230 can be connected.



**Item no. 89472**

EAN: 4043619894727

Country of origin: Taiwan, Republic of China

Package: Retail Box

## Technical details

- Connector:
  - internal:
    - 1 x 67 pin M.2 key M slot
    - 1 x PCI Express x4, V4.0
- Interface: PCIe
- Supports M.2 modules in format 22110, 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe
- Maximum height of the components on the module: 1.5 mm  
application of double-sided assembled modules supported
- Supports NVM Express (NVMe)


## System requirements

- Windows 7/7-64/8/8-64/8.1/8.1-64/10/10-64, Linux Kernel 3.19
- PC with one free PCI Express x4 / x8 / x16 / x32 slot

## Package content

- PCI Express card
- Low profile bracket
- 1 x fixing screw
- User manual

## Images



## General

Form factor:	Low Profile
Supported operating system:	Linux Kernel 3.19 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Slot:	PCIe
Supported module:	M.2 modules in format 22110, 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported

## Interface

Internal:	1 x 67 Pin M.2 NGFF key M slot 1 x PCI Express x4, V4.0
-----------	--

## Technical characteristics

Data transfer rate:	up to 39 Gbps
---------------------	---------------