


# Delock PCI Express x1 Card to 2 x Serial RS-232

## Description

The PCI Express card by Delock expands a PC by two external serial RS-232 ports. Different devices such as scanner, protocol converter, IoT devices etc. can be connected to this card. By using the included low profile brackets, the PCI Express card can be also installed into a Mini-PC.



**Item no. 89918**

EAN: 4043619899180

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - external: 2 x serial RS-232 DB9 male
  - internal: 1 x PCI Express x1, V1.1
- Chipset: WCH CH382L
- Compatible with 16C550 UART
- Buffer: 256 byte on each port
- Databits: 5, 6, 7, 8
- Stop bits: 1, 2
- Parity: even, odd, none, mark, space
- Flow control: none, hardware RTS / CTS, software XON / XOFF


## System requirements

- Linux Kernel 4.15 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- PC with one free PCI Express slot

## Package content

- PCI Express card
- 2 x low profile bracket
- Driver CD
- User manual

## Images



## General

Form factor:	Low Profile (MD1)
Specification:	RS-232 (EIA / TIA) PCIe 1.1
Supported operating system:	Linux Kernel 4.15 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11
Slot:	PCIe

## Interface

External:	2 x serial RS-232 DB9 plug
Internal:	1 x PCI Express x1, V1.1

## Technical characteristics

Chipset:	WCH CH382L
Data transfer rate:	2 x up to 230,4 Kbps
UART:	16C550

## Physical characteristics

Slot bracket:	Low Profile standard
Colour:	green