

Delock PCI Express x1 Card to 4 x external USB Type-A female SuperSpeed USB (USB 3.2 Gen 1)

Description

The PCI Express card by Delock expands a PC by **four external USB 3.2 Gen 1 ports**. Different USB devices such as docking stations, card reader, external enclosure etc. can be connected.

10 Watt output power per port

The card requires no additional power supply and can still supply **2 A at each port**. Thus, a total of 8 A can be achieved when all ports are used.



Item no. 90509

EAN: 4043619905096

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - external: 4 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
 - internal: 1 x PCI Express x1, V2.0
- Chipset: Renesas D720201
- Data transfer rate up to:
 - SuperSpeed 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- Electrical power per port: max. 10 watt (5 V / 2 A)
- Bootable
- Operating temperature: 0 °C ~ 40 °C
- Storage temperature: -10 °C ~ 70 °C
- Relative humidity: 10 - 90 % (non condensing)


System requirements

- Linux Kernel 3.18 or above
- Windows 8.1/8.1-64/10/10-64
- PC with one free PCI Express slot

Package content

- PCI Express card USB 3.2 Gen 1
- 1 x screw
- User manual

Images



General

Supported operating system:	Linux Kernel 3.18 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
-----------------------------	------------------------------------------------------------------------------------------------------------------

Interface

External:	4 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
Internal:	1 x PCI Express x1, V2.0

Technical characteristics

Chipset:	Renesas D720201
----------	-----------------

Physical characteristics

Slot bracket:	standard
---------------	----------